
Parallel Graph Algorithms (continued)

MaxFlow



- A flow network G=(V,E): a directed graph, where each edge (u,v) ∈ E has a nonnegative capacity c(u,v)>=0.
- If $(u,v) \notin E$, we assume that c(u,v)=0.
- Two distinct vertices : source s and sink t.

Find f: E -> R, such that

Capacity constraint: For all u,v ∈ V, we require f(u,v) ≤ c(u,v)
Flow conservation: For all u ∈V\{s,t}, we require ∑_{e inv} f(e) = ∑_{e out v} f(e)

• Maximize $|f| = \sum_{v \in V} f(s, v)$

A Long History

Initially defined by Ford and Fulkerson (1956)

Date Discoverer		Running time	
1969	Edmonds and Karp	$O(nm^2)$	
1970	Dinic	$O(n^2m)$	
1974	Karzanov	$O(n^3)$	
1977	Cherkasky	$O(n^2 m^{1/2})$	
1978	Malhotra, Pramodh Kumar,	$O(n^3)$	
	and Maheshwari		
1978	Galil	$O(n^{5/3}m^{2/3})$	
1978	Galil and Naamad; Shiloach	$O(nm(\log n)^2)$	
1980	Sleator and Tarjan	$O(nm \log n)$	
1982	Shiloach and Vishkin	$O(n^3)$	
1983	Gabow	$O(nm \log U)$	
1984	Tarjan	$O(n^3)$	
1985	Goldberg	$O(n^3)$	
1986	Goldberg and Tarjan	$O(nm \log(n^2/m))$	
1986	Ahuja and Orlin	$O(nm + n^2 \log U)$	

MaxFlow for sparse digraphs with m edges and integer capacities between 1 and C

1997	length function	$O(m^{3/2}\log m\log C)$	Goldberg-Rao
2012	compact network	$O(m^2 / \log m)$	Orlin
?	?	<i>O</i> (<i>m</i>)	?

Applications


- Data mining.
- Open-pit mining.
- Bipartite matching.
- Network reliability.
- Baseball elimination.
- Image segmentation.
- Network connectivity.

- Distributed computing.
- Security of statistical data.
- Egalitarian stable matching.
- Network intrusion detection.
- Multi-camera scene reconstruction.
- Sensor placement for homeland security.
- Many, many, more.

Example: Matching


Given an undirected graph G = (V, E) a subset of edges $M \subseteq E$ is a matching if each node appears in at most one edge in M.

Max matching: Given a graph, find a max cardinality matching.



Bipartite Matching


A graph G is bipartite if the nodes can be partitioned into two subsets L and R such that every edge connects a node in L to one in R



Note that nodes 2, 5, 3' and 4' are **not covered**

Bipartite Matching: Maxflow Formulation

- Create digraph $G' = (L \cup R \cup \{s, t\}, E')$.
- Direct all edges from L to R, and assign infinite (or unit) capacity.
- Add source s, and unit capacity edges from s to each node in L.
- Add sink t, and unit capacity edges from each node in R to t.



Solving MaxFlow: The Ford-Fulkerson method

The Ford-Fulkerson method depends on three important ideas that transcend the method and are relevant to many flow algorithms and problems: residual networks, augmenting paths, and cuts. These ideas are essential to the important max-flow min-cut theorem, which characterizes the value of maximum flow in terms of cuts of the flow network.

Augmenting Paths

- Given a flow network and a flow, the residual network consists of edges that can admit more net flow.
- The amount of additional net flow from u to v before exceeding the capacity c(u,v) is the residual capacity of (u,v), given by:
 c_f(u,v)=c (u,v) f (u,v)

and in the other direction:

 $c_f(v, u) = c(v, u) + f(u, v).$

• If f is a flow in G and f' is a flow in the residual network G_f then f + f' is also a valid flow in G

Augmenting Paths

- Given a flow network G=(V,E) and a flow f, an augmenting path is a simple path from s to t in the residual network G_f.
- Residual capacity of p : the maximum amount of net flow that we can ship along the edges of an augmenting path p, i.e.,

 $c_f(p)=\min\{c_f(u,v):(u,v) \text{ is on } p\}.$

 $2 \rightarrow 3 \rightarrow 1 \rightarrow 0$

The residual capacity is 1


The basic Ford-Fulkerson algorithm

FORD-FULKERSON(*G*,*s*,*t*) for each edge $(u,v) \in E[G]$ do f[u,v] = 0f[v,u] = 0


while there exists a path p from s to t in the residual network G_f

do $c_f(p) = \min\{c_f(u,v): (u,v) \text{ is in } p\}$ for each edge (u,v) in p do $f[u,v] = f[u,v]+c_f(p)$

Why for every edge (u,v) : (v,u)?




Why for every edge (u,v) : (v,u)?




Augmented path with residual capacity = min(5,5,1) = 1


Why for every edge (u,v) : (v,u)?




Why for every edge (*u*,*v*): (*v*,*u*)?





No Augmented Path possible anymore. OPTIMAL FLOW = 5 ????







Augmented path with residual capacity = min(5,5,1) = 1






Now Still Augmented Paths POSSIBLE !!!!!!!





MaxFlow = 6 !!!!!!





FINAL SOLUTION f + f'


More Complex Execution

In the following slides:


(a)-(d) Successive iterations of the while loop: The left side of each part shows the residual network G_f from line 4 with a shaded augmenting path p. The right side of each part shows the new flow f that results from adding f_p to f. The residual network in (a) is the input network G. (e) The residual network at the last while loop test. It has no augmenting paths, and the flow f shown in (d) is therefore a maximum flow.








(c)





(e)

NO AUGMENTED PATH FOUND

The Edmonds-Karp algorithm A practical implementation of Ford Fulkerson

- Find the augmenting path using breadth-first search.
- Breadth-first search gives the shortest path for graphs. (Assuming the length of each edge is 1.)
- Time complexity of Edmonds-Karp algorithm is O(VE²).
- The proof is very hard and is not required here.

Relationship with Cut Sets

A cut in a network with source s and sink t is a subset $X \subset V$, such that

 $s \in X$ and $t \notin X$

(X, $V \setminus X$) is the set of edges from a vertex in X to a vertex in $V \setminus X$

The capacity of a cut X equals:

$$C(X) = \sum_{x \in (X, V \setminus X)} c(x)$$

For every flow $f: E \rightarrow R$ and cut X,

$$\left|f\right| \leq C(X)$$

Max Flow == Min Cut

Theorem 1: A flow in a network G is maximal iff there exists no augmenting path in G

Theorem 2: The maximal flow in a network G equals the minimal capacity cut set of G

Proof (sketch) Given that f is a maximal flow in G. Construct X such that s ε X, and for all v for which there exists an augmenting path from s to v: v ε X. Then t cannot belong to X, because there is no augmenting path anymore. So X is a proper cut of G. So C (X) = |f| and $|f| \leq C$ (Y) for any cut Y. So X is the minimal cut. The reverse follows trivially.

Push-Relabel Algorithm by Goldberg and Tarjan (JACM 1988)

- Input: network (G = (V, E), s, t, c)
- $\bullet \ h[s]:=|V|$
- for each $v \in V \{s\}$ do h[v] := 0
- for each $(s,v) \in E$ do f(s,v) := c(s,v)
- while f is not a feasible flow

- let c'(u,v) = c(u,v) + f(u,v) - f(v,u) be the capacities of the residual network

- if there is a vertex $v \in V \{s, t\}$ and a vertex $w \in V$ such that $e_f(v) > 0$, h(v) > h(w), and c'(v, w) > 0 then
 - * push $\min\{c'(v, w), e_f(v)\}$ units of flow on the edge (v, w)
- else, let v be a vertex such that $e_f(v) > 0$, and set h[v] := h[v] + 1


• output f

Note c'(u,v) = the residual capacity of the back-edge of (u,v), so an edge going from v to u. The update of the remaining capacity of (u,v) is done on c(u,v)!!!


The labeling function *h*

- Only flow can be pushed from a node v to w if
 h(v) > h(w)
- Once raised, *h*(*v*) will never be decremented
- Ping Pong effects are avoided
- The algorithm will actually finish


Example




Excess flow is pushed to a




First h[a] is incremented to 1 and then excess flow is pushed from a to b and d




h[a] is incremented to 7!! then excess flow is pushed (back) from a to s




First h[b] is incremented to 1, then excess flow is pushed from b to c and t




First h[c] is incremented to 1, then excess flow is pushed from c to d




First h[d] is incremented to 1, then excess flow is pushed from d to t



b is the only node with excess > 0, b has no outgoing residual edges, so h[b] is incremented to 8 and b will push **back** excess flow to a



node a is the only active node with excess flow > 0 and will push flow back to s



A parallel version of push relabel

